

**PRODUCT
DATA SHEET**

DESIGN 150
Vinyl Collection 2012

January 2012

Type of flooring

EN 653

Vinyl Floorcovering

Class of use

EN 685



Class

22

Description



EN 428

1,50 mm



EN 429

0,20 mm



EN 660-2

Abrasion group

T



EN 430

1,155 kg/m²



EN 426

**35 m
4+3+2m**



EN ISO 717/2

14 dB

Impact sound
absorption



EN 433

≤ 0,35 mm

Static
indentation

Optional Characteristics



ISO 105/B02

Light fastness

≥ 6



EN 1815

Static electrical
propensity

≤ 2 kV



Fire Classification

EN 13501-1

Bfl-s1

Report N° :

RA10-0251



EN 434

Dimensional
stability

≤ 0,40 %



Recyclable

OK



EN 423

Chemical
resistance

OK



Slip resistance

EN 13893
DIN 51130

**≥ 0,30 μ
R10**



EN 12524

Thermal resistance
for underfloor heating

0,02 m²/kW



EN 14041 : 2004

**Manufactured in EEC by
TARKETT**

DESIGN 150	TARKETT BALANCED CHOICE	58 % Natural	100 % Recyclable	Better Indoor Air Quality *TVOC AT 28 DAYS
-----------------------	--	-----------------	---------------------	--