

SPECIFICATIONS	www.euroflor.nz	EUROFLOR
HARD INTERLOCKING TILES	LIGHT COMMERCIAL	HEAVY COMMERCIAL
A CERTIFICATIONS & CLASSIFICATIONS	STANDARD	IMPACT RESONATE®
TYPE OF FLOOR COVERING	ISO 10582	HARD INTERLOCKING TILES
CE CERTIFICATION	EN 14041	Yes
CLASSIFICATION	EN ISO 10874	Heavy Traffic : Class 33
TECHNICAL CHARACTERISTICS	STANDARDS	IMPACT RESONATE®
TOTAL THICKNESS	EN ISO 2436 (EN428)	5.0MM
WEAR LAYER THICKNESS	EN ISO 24340 (EN429)	0.50MM
SURFACE TREATMENT	UV TREATED	PUR
TOTAL WEIGHT	EN ISO 23997 (EN430)	8000 g/m ²
WEAR LAYER BINDER CONTENT	ISO 10582	TYPE 1
FORM OF DELIVERY (PLANK BOX)	EN ISO 24342 (EN427)	10 PIECES /BOX 218 X 1210 = 2.64m ²
TECHNICAL PERFORMANCES	STANDARDS	IMPACT RESONATE®
DIMENSIONAL STABILITY	EN ISO 23999 (EN434)	≤0.10%
REACTION TO FIRE	EN 13501 - 1	Bfl- S1 GLUED OVER A2fl
RESIDENTIAL INDENTATION	EN ISO 24343-1	REQUIRED VALUE ≤0.10mm
FURNITURE LEG	EN 424	NO DAMAGE
CASTOR CHAIR	EN ISO 4918 (EN425)	NO DAMAGE
CURL RESULTANT TO HEAT	EN ISO 23999 (EN434)	≤ 2mm
THERMAL RESISTANCE	EN ISO 10456	0.07M2K/W
IMPACT SOUND REDUCTION	EN ISO 140-8	W =11Db
LIGHT FASTNESS	EN ISO 105 - B02	PASS
RESISTANCE TO CHEMICALS	EN ISO 26987 (EN423)	GOOD RESISTANCE
SLIP RESISTANCE	DIN51130 EN 13893	R9 PASS
ELECTRICAL PROPERTIES	EN 1815 EN 1081	< 2kV ON CONCRETE R1>1010Ω
* The above data is valid at the the time of print		